



COPERNICUS II GPS RECEIVER

KEY FEATURES

- 2.54 mm T x 19 mm W x 19 mm L
- -160 dBm tracking sensitivity
- 132 mW typical continuous tracking
- Fast TTFF (cold start): 38 sec
- Supports SBAS (WAAS, EGNOS, MSAS)
- Active or passive antennas
- NMEA, TSIP, TAIP protocols
- RoHS-Compliant (Pb-free)
- 2G dynamics
- Stable indoor PPS in Stationary Mode



ULTRA-THIN, LOW POWER, SURFACE MOUNT GPS MODULE

Drop-in Performance

The Trimble® Copernicus® II GPS receiver delivers proven performance and Trimble quality for a new generation of position-enabled products. It features the TrimCore™ navigation software for extremely fast startup times and high performance in foliage canopy and urban canyon environments.

The Copernicus II is compatible with all applications using the previous generation of Copernicus module*. The Copernicus II module is a complete 12-channel GPS receiver in a 19 mm x 19 mm x 2.54 mm thumbnail-sized module. The module is packaged in tape and reel for high speed pick-and-place manufacturing processes; 28 edge castellations provide RF and I/O interface without the need for connectors. Each module is manufactured and tested to Trimble's highest quality standards.

The sensitive Copernicus II GPS receiver can autonomously acquire GPS satellite signals and quickly generate reliable position fixes in extremely challenging environments and under poor signal conditions. The unit also accepts aided GPS (A-GPS) data for faster startups in very weak conditions.

In Stationary Mode the Copernicus II GPS receiver can produce an accurate and stable PPS with an indoor antenna

Features include:

- Self survey
- TRAIM on clock and frequency
- Noise filter to reduce PPS variance

The Copernicus II GPS module is a complete drop-in, ready-to-go receiver that provides position, velocity, and time data in a user's choice of three protocols. Trimble's powerful TSIP protocol offers complete control over receiver operation and provides detailed satellite information. The TAIP protocol is an easy-to-use ASCII protocol designed specifically for track and trace applications. The bi-directional NMEA 0183 v3.0 protocol offers industry-standard data messages and a command set for easy interface to mapping software.

Applications

Compatible with active or passive antennas, the Copernicus II GPS receiver is perfect for portable hand-held, battery-powered applications. The receiver's small size and low power requirement make it ideal for use in portable appliances, sport accessories, personal navigators, cameras, computer, and communication peripherals, as well as vehicle tracking, navigation, and security applications.

COPERNICUS II GPS RECEIVER

PERFORMANCE SPECIFICATIONS

Accuracy (24 hr static)
 Horizontal. <2.5 m 50%, <5 m 90%
 SBAS <2.0 m 50%, <4 m 90%
 Altitude. <5 m 50%, <8 m 90%
 SBAS <3 m 50%, <5 m 90%
 Velocity 0.06 m/sec
 Static PPs. ±60ns RMS
 PPS (Stationary Mode "indoor" @ -145dBm) ±350ns

Acquisition (Autonomous, -130dBm, 50%)
 Reacquisition 2 s
 Hot Start 3 s
 Hot Start without battery backup 8 s*
 Warm Start 35 s
 Cold Start 38 s

Sensitivity (unaided)
 Tracking -160 dBm
 Acquisition -148** dBm

Receiver Dynamics 2G

* Ephemeris not older than 4 hours.
 **For hot start with ephemeris otherwise -144 dBm

INTERFACE CHARACTERISTICS

Connections 28 surface-mount edge castellations
 Serial Port 2 serial ports
 PPS. 3.0 V CMOS-compatible pulse, once per second
 Protocols TSIP, TAIP, NMEA 0183 v3.0
 Bi-directional NMEA messages
 Messages selectable by NMEA commands
 Selection stored in flash memory

ELECTRICAL CHARACTERISTICS

Prime Power +2.7 V DC to 3.3 V DC
 Power Consumption (typ.) 44 mA (132 mW) @ 3.0 V
 Backup Power. +2.7 V DC to +3.3 V DC
 Ripple Noise Max 50 mV, peak-to-peak from 1 Hz to 1 MHz

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature. -40 °C to +85 °C
 Storage Temperature. -55 °C to +105 °C
 Vibration
 0.008 g2/Hz. 5 Hz to 20 Hz
 0.05 g2/Hz. 20 Hz to 100 Hz
 -3 dB/octave 100 Hz to 900 Hz
 Operating Humidity. 5% to 95% R.H. non-condensing, at +60 °C

PHYSICAL CHARACTERISTICS

Enclosure. Metal shield
 Dimensions 19 mm W x 19 mm L x 2.54 mm H
 (0.75 in W x 0.75 in L x 0.1 in H)
 Weight <2 g (0.07 oz) including shield

PINOUT ASSIGNMENTS

GND	1	28	GND
GND	2	27	GND
RF-IN	3	26	Reserved
GND	4	25	Reserved
LNA	5	24	TXD-B
VBAT	6	23	TXD-A
Open	7	22	Reserved
Short	8	21	RXD-A
Reserved	9	20	RXD-B
Reserved	10	19	PPS
Xreset	11	18	Reserved
Vcc	12	17	Reserved
GND	13	16	Xstandby
GND	14	15	GND

ORDERING INFORMATION & ACCESSORIES

Module available as 20 piece module package for evaluation
 Tape on reel (100 pieces)
 Tape on reel (500 pieces)

Reference Board Copernicus II GPS module mounted on a carrier board with I/O and RF connectors, including the RF circuitry with the antenna open detection, as well as antenna short detection and protection.

Starter Kit Includes Copernicus II Reference Board mounted on interface motherboard in a durable metal enclosure, 3 additional Copernicus II modules (63530-00), AC/DC power converter, compact 3V magnetic-mount GPS antenna with MCX connector and 5m cable. Also comes with USB interface cable, cigarette lighter adapter, TSIP, NMEA, and TAIP protocols. Software Tool Kit is available from the Trimble Support page.

FEATURE DIFFERENCE TABLE	63530-00	63530-10	67415-00
Standby Serial Command Supported	No	Yes	No
SHORT pin can be pulled HIGH when not used	Yes	Yes	No (SHORT must be "no connect" if not used)

PRODUCT	PART NUMBER	MOQ PACKAGING OPTIONS
Copernicus II	63530-00	20 piece tray, 100 or 500 piece reels
Copernicus II with Soft Shutdown feature supported	63530-10	20 piece tray, 100 or 500 piece reels
Copernicus IIA	67415-00	20 piece tray, 100 or 500 piece reels
Copernicus II reference board	63531-00	1 reference board
Copernicus II Starter Kit	63532-05	1 starter kit
3V Magnetic Mount Antenna, MCX	66800-50	20, 80 or 400 antennas
3V Magnetic Mount Antenna, SMA	66800-52	20, 80 or 400 antennas

Parts of this product are patent protected.

Trimble has relied on representations made by its suppliers in certifying this product as RoHS compliant.

Specifications subject to change without notice.

Trimble Navigation Limited is not responsible for the operation or failure of operation of GPS satellites or the availability of GPS satellite signals.

*63530-10 version

NORTH AMERICA

Trimble Navigation Limited
 Corporate Headquarters
 935 Stewart Drive
 Sunnyvale, CA 94085
 +1-800-787-4225 Phone
 +1-408-481-7741 Phone
 Email: AD_Sales@trimble.com

EUROPE

Trimble Navigation Europe
 +4670-544-10-20 Phone

KOREA

Trimble Export Ltd, Korea
 +82-2-555-5361 Phone

CHINA

Trimble Navigation Ltd, China
 +86-10-8857-7575 Phone

